



**Colour selectable switch**

DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
<ul style="list-style-type: none"> <li>• Flange size 230mmØ</li> <li>• 600mml cordset.</li> <li>Hole cut: 200</li> <li>Cavity depth: 150</li> <li>Side clearance: 50</li> </ul>	<ul style="list-style-type: none"> <li>Total lumens: 2580</li> <li>Power supply: 220-240V</li> <li>Dimmable: Yes</li> <li>CRI: 80</li> <li>Wattage: 25</li> <li>Beam angle: 60°</li> <li>Control gear: Included</li> </ul>	<ul style="list-style-type: none"> <li>• Low glare and colour selectable LED downlight.</li> <li>• It's advanced reflector has a less than 19% glare- compliant to UGR&lt;19 standard.</li> <li>• Choose from 3,000K, 4,000K or 5,700K colour temperatures at the flick of a switch.</li> <li>• Use the AS saftey approved cordset supplied or hardwire to TPS using easy to wire extra large terminals.</li> <li>• Total Lumens: 2250-2580</li> </ul>	<ul style="list-style-type: none"> <li>Lamp included: Yes</li> <li>Number of lamps: 1</li> <li>IP Rating: IP54</li> <li>Technology field: LED</li> <li>Indoor / Outdoor: Indoor</li> <li>Mounting type: Ceiling</li> <li>Colour: White</li> </ul>